



CALCIUM SULPHATE PANEL

TOP & BOTTOM WITH GALVANIZED STEEL
(Gravity Lay And/Or Corner Style)


Panel Structure

Pre-fabricated Calcium sulphate panel core encapsulated with 0.4mm and 0.4mm galvanized steel on top and bottom.

Advantage

High loading capacity with improved lateral stability with either gravity lay or corner lock style due to profiles chamfered edge finish. Non-Susceptible to humidity and moisture.

Non-combustible and 100% fully recyclable at end of life cycle.

TYPE		Galvanized LHG760 (2019) (0.4/0.4)
Panel Size		600mm x 600mm x 26mm
Core Density		1800 kg /m3
Concentrated Load	N	5560
	KG	567
Impact Load	N	780
Ultimate Load - Point	N	13500
Ultimate Load - UDL	N	36000
Rolling Load /N	10 times	5560
	10,000 times	4450
Reaction to Fire		A1 / Class 0 + 1
Weight per Panel	KG	17.80
Pedestal and Stringer 		Used in standard installations 100mm x 100mm x 2.5mm base plate M16 screw lock nut with secure engagement channels
Application		High Density / populated commercial offices buildings. Panel ideal for carpet tile, vinyl or other soft floor finish applications


PRODUCT DATASHEET DEVAR - GALVANIZED LHG760 / (2019)



MATCH IN ONE SQM :

- PANEL 2.78 PCS
- PEDESTAL 3.36 PCS
- SCREW 11.2 PCS

20FT GP CAPACITY: 420 M2



DEVAR HOLDINGS LIMITED

Tel: (852) 3108 2108
Fax: (852) 3108 2100

www.devargroup.com.hk
enquiries@devargroup.com.hk