

Specification:

Calcium Sulphate / Cementitious System

DIMENSIONS	600mm x 600mm x 30.0mm / 33.5mm / 39.3mm	INTERIOR	Calcium Sulphate / Cementitious Core
EXTERIOR	Fully Steel Encapsulated	FINISH	Powder Coated or Galvanised Steel

TYPE	AREA OF USE	SYSTEM WEIGHT	PANEL SYSTEM		UNIFORMLY DISTRIBUTED LOAD		SAFETY FACTOR		OVER 25mm SQUARE		PANEL DEFLECTION AFTER 24 HOURS		PANEL SQUARENESS		CONCAVITY & CONVEXITY	
			Gravity Lay	Corner Lock	PSA Spec	Devar Spec	PSA Spec	Devar Spec	PSA Spec	Devar Spec	PSA Spec	Devar Spec	PSA Spec	Devar Spec	PSA Spec	Devar Spec
PANEL NUMBER	PSA Description	Total	Availability		kN/m ²	Load		kN		mm		%		mm		
LIGHT GRADE DLG580	General office areas with no heavy equipment	36.30	Yes	Yes	≥ 6.70	11.11	3 x load for 5 mins	✓	≥ 1.50	3.11	≤ 2.40	✓	≤ 0.06	✓	≤ 0.75	✓
MEDIUM GRADE DMG670	General office areas with heavy equipment	39.30	Yes	Yes	≥ 8.00	12.44	3 x load for 5 mins	✓	≥ 3.00	3.55	≤ 2.40	✓	≤ 0.06	✓	≤ 0.75	✓
HEAVY GRADE DHG760	Computer rooms, telecom switch rooms, etc	41.70	Yes	Yes	≥ 12.00	15.55	3 x load for 5 mins	✓	≥ 4.50	4.50	≤ 2.40	✓	≤ 0.06	✓	≤ 0.75	✓
EXTRA HEAVY GRADE DXL850	Specialist applications	44.60	Yes	Yes	≥ 12.00	17.78	3 x load for 5 mins	✓	≥ 4.50	5.55	≤ 2.40	✓	≤ 0.06	✓	≤ 0.75	✓

✓ = meets or exceeds standards

Delivery on Time - Everytime

DEVAR ACCESS FLOORING

Level 19, 2 IFC, 8 Finance Street, Central, Hong Kong.

Tel: (+852) 3108 2108 • Email: enquiries@devargroup.com.hk • Web: www.devargroup.com.hk

n55Plus

RIBA 註冊

riba
product
selector



SGS